

## 4' WIDE SA PRO SERIES

4' Wide SA Standard Specifications				
	4 x 6 SA	4 x 8 SA	4 x 10 SA	
Overall Length	122 1/2"	146 1/2"	168 1/2"	
Width	64"	64"	64"	
Height	69 1/2"	69 1/2"	69 1/2"	
Interior Length	6' 7"	8' 7"	10' 7"	
Width	45 1/2"	45 1/2"	45 1/2"	
Height	48"	48"	48"	
Platform Height	19 3/4"	19 3/4"	19 3/4"	
Axles	Spring	Spring	Spring	
Brakes	N/A	N/A	N/A	
Frame	2" x 3"	2" x 3"	2" x 3"	
Tire Size	530 x 12	530 x 12	530 x 12	
Hitch Ball Size	2"	2"	2"	
Curb Weight (#)	540	690	840	
Hitch Weight (#)	50	65	80	
GVWR (#)	2000	2000	2000	
Payload Capacity (#)	1460	1310	1160	
Rear Doors	Single	Single	Single	
Opening Width	38"	38"	38"	
Opening Height	42 1/2"	42 1/2"	42 1/2"	
Exterior	.030 Smooth	.030 Smooth	.030 Smooth	
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	
Sidewalls (16" O.C.)	3/16 Luan	3/16 Luan	3/16 Luan	

### 00-9004 4X SA Standard Features

- 2" X 3" Welded Tubular Steel Main Frame
- 2" Coupler With Single Tube Tongue
- 2000# Dexter Spring Axle With E-Z Lube Hubs
- 5.30 X 12 LRC Tires
- 4 Way Flat Electrical Plug
- 3/4" Advantech Floor (24" O/C)
- 3/16" Luan Plywood Walls (16" O/C)
- .030 Smooth Aluminum Exterior
- Painted Aluminum Rear Header
- Round Top With Fiberglass Front Cap
- 1 Piece Seamless Aluminum Roof
- Brushed Aluminum Fenders
- Single Rear Door With Bar Lock
- Zinc Coated Door Hardware
- DOT Approved Lighting and Safety Equipment
- Limited 5 Year Warranty