

## 6' WIDE TA PRO SERIES (8' TO 14')

6' Wide TA Standard Specifications					
	6 x 8 TA	6 x 10 TA	6 x 12 TA	6 x 14 TA	
Overall Length	12' 5"	14' 5"	16' 5"	18' 5"	
Width	93"	93"	93"	93"	
Height	93"	93"	93"	93"	
Interior Length	8' 8"	10' 8"	12' 8"	14' 8"	
Width	69 1/2"	69 1/2"	69 1/2"	69 1/2"	
Height	72"	72"	72"	72"	
Platform Height	19"	19"	19"	19"	
Axes	Torsion	Torsion	Torsion	Torsion	
Brakes (4-Way)	Electric	Electric	Electric	Electric	
Frame	2" x 4"	2" x 4"	2" x 4"	2" x 4"	
Tire Size	ST225/75D15	ST225/75D15	ST225/75D15	ST225/75D15	
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	
Curb Weight (#)	1500	1620	1740	1860	
Hitch Weight (#)	125	165	215	285	
GVWR (#)	7000	7000	7000	7000	
Payload Capacity (#)	5500	5380	5260	5140	
Rear Doors	Double	Double	Double	Double	
Opening Width	62"	62"	62"	62"	
Opening Height	65 1/2"	65 1/2"	65 1/2"	65 1/2"	
Exterior	.030 Smooth	.030 Smooth	.030 Smooth	.030 Smooth	
Floor (24" O.C.)	3/4" Advantech	3/4" Advantech	3/4" Advantech	3/4" Advantech	
Sidewalls (16" O.C.)	3/8" Plywood	3/8" Plywood	3/8" Plywood	3/8" Plywood	

### 00-9007 6X TA Standard Features

- 2" X 4" Welded Tubular Steel Main Frame
- 2 5/16" Coupler With A-Frame
- 3500# Dexter Torsion Axles With E-Z Lube Hubs
- ST225/75D15 LRC Tires
- 4 Way Electric Brakes
- Gel Cell Rechargeable Breakaway Kit
- 7 Way Electrical Plug
- 3/4" Advantech Floor (24" O/C)
- 3/8" Exterior Grade Plywood Walls (16" O/C)
- .030 Smooth Aluminum Exterior
- Painted Aluminum Rear Header
- Round Top With Fiberglass Front Cap
- Seamless Aluminum Roof And Radius Wrap
- Brushed Aluminum Fenders
- 24" Gravel Guard With Bottom Trim
- 32" Curbside Door With Bar Lock
- Double Rear Doors With Cam Lock
- Zinc Coated Door Hardware
- 12 Volt Dome Light With Wall Switch
- DOT Approved Lighting and Safety Equipment
- Limited 5 Year Warranty